

# Line Replaceable Contactors (LRC)

The Z and W series of lightweight, rugged AC contactors offer a plug-in plunger interface and are designed to withstand severe vibration, shock and thermal environments. They are rated at 115/200 VAC, 50 to 400 amps, 400 Hz, 3Ø.



Model W-X9N



Model Z-X9N

## Applications

- Aircraft
- High-reliability applications

## Features

- Compact, lightweight design
- High reliability
- Proven balanced-force design
- Multiple auxiliary contacts
- Fast operate and release times
- Multiple coil configurations
- Meets MIL-R-6106 requirements
- Designed for "quick change" installation
- Ship-side mounting interface available
- Gasket-sealed mounting

## Dimensions / Weight

- **Model W-X9N**  
4.43" x 4.43" x 3.42" (LxWxH)  
3 lbs. 8 oz
- **Model Z-X9N**  
3.63" x 3.63" x 3.42" (LxWxH)  
2 lbs. 6 oz

*Leach International Corporation, founded in 1919, is a world leader in the design and manufacture of electrical switching and control devices for the aerospace and rail industries.*

**LEACH®** INTERNATIONAL

Solutions for Power Switching and Control

[www.leachintl.com](http://www.leachintl.com)

Leach International  
Europe S.A.

2 Rue Goethe  
F-57430 Sarrelbe  
France

Leach International  
North America

6900 Orangethorpe Avenue  
P.O. Box 5032  
Buena Park, CA 90622-5032  
USA

Leach International  
Asia-Pacific Ltd.

20th Floor, Flat A  
Shing Hing Commercial Building  
21-27 Wing Kut Street  
Central, Hong Kong